## 53' GOOSENECK CHASSIS

CARRIES 1x 53' ISO DOMESTIC CONTAINER

COMPLIES TO ALL TOFC, AAR, DOT, FMVSS, ISO, SAE AND TTMA REQUIREMENTS.





### **FUNCTIONAL ACCESSORIES**

KINGPIN	JOST (USA) 2" AAR APPROVED WELDED TYPE
LANDING GEAR	JOST (USA) A440 MAGNUM - 17" TRAVEL, 2 SPEED WITH T FOOT

#### **RUNNING GEARS**

AXLES	SAF (INDIA) " ROUND AXLES, 22,500 LBS CAPACITY, 71.5" TRACK WITH 16.5 X 7" Q BRAKES
HUBS AND DRUM	10 STUD HUB PILOTED WITH OUTBOARD CAST STEEL DRUMS
SUSPENSION	HUTCH (USA) 9700 SERIES 49" SPACING SUSPENSION WITH 354 HIGH ARCH SPRINGS

# **BRAKE SYSTEM**

ABS SYSTEM	KNORR BREMSE (USA) 2S/1M ABS
BRAKE ACTUATORS	HALDEX (MEXICO) 30/30 SB ACTUATORS
AUTO SLACKS	HALDEX (INDIA) AUTO SLACKS

#### **ELECTRICAL SYSTEM**

HARNESSES	PHILLIPS (MEXICO) 12 VOLT MODULAR HARNESS
LIGHTS	PHILLIPS (USA) PERMALITE LED – MARKER LAMPS AND 4" ANTI THEFT STOP – TURN TAIL LAMPS

#### **RIMS & TIRES**

RIMS	ASIA WHEELS (THAILAND) 8.25 X 22.5 WHITE POWDER COATED STEEL WHEELS OPTION: ALLOY RIMS (MALAYSIA)
TIRES	WESTLAKE (THAILAND) CR915 11 R 22.5 14 PR TIRES

# **STRUCTURE**

GOOSENECK MATERIAL	HOT ROLLED ASTM A572 GR50 / SM490YA SHEETS (THAILAND)	
MAIN BEAM MATERIAL	HOT ROLLED 12" - 16 LBS/ FT - ASTM A992 GR 50 (THAILAND)	
GOOSENECK BEAM	4" HIGH X 4" WIDE FABRICATED I BEAM	
CROSS MEMBER	3/16" THICK X 3" WIDE X 9" HIGH CHANNEL SUPPORTED WITH GUESSETS	
FRONT BOLSTER	¼" THICK 8" WIDE X 10" HIGH WITH TAPER IN FULL LENGTH FOR GATHERING CONTAINER IN OPERATION WITH CORNER CASTINGS	
REAR BOLSTER	¼" THICK C CHANNEL AND 5/16" TOP PLATE WITH CORNER NON RETRACTABLE TWIST LOCKS	
SLIDER SYSTEM	FABRICATED STRUCTURE ACTUATED BY 2 / 4 MECHANICAL LOCKING PINS AT THE FRONT OF SLIDER WITH INDEXING HOLES AR 4" / 5" APART	
REAR BUMPER	4" X 4" BOLT ON ICC REAR BUMPER	

#### **CHASSIS COATING SYSTEM**


PRIMER	2 MILS OF ZINC ENRICHED PRIMER FROM SHERWIN WILLIAMS
TOP COAT	2 MILS OF PU TOP COAT IN COLOR OF CHOICE FROM SHERWIN WILLIAMS


# **OTHER FEATURES**


PHILLIPS (USA) DOCUMENT HOLDER	BOLT ON TWIST LOCKS, BOLT ON ICC BUMPERS	' I BOLLON
ANTI SAIL MUDFLAPS,	PSI – ATIS,	GEAR
DOT C2 TAPES	GRADE 8.8 FASTENERS	BRACKETS


<sup>\*</sup>APPROX WEIGHT WITHIN ± 2% OF THE MENTIONED VALUE














\*APPROX WEIGHT WITHIN ± 2% OF THE MENTIONED VALUE

DIMENSIONS	
OVERALL LENGTH	53' 10-5/8"
OVERALL WIDTH	96"
FIFTH WHEEL HEIGHT	48" ± 1"
REAR DECK HEIGHT	48" ± 1"
TARE WEIGHT	7,700 LBS ± 2%
GVWR	74,900 LBS

Email: TrendChassis@TrendChassis.com Tel: 1-855-777-8217

www.trendchassis.com